

## SINGLE ENCLOSURE GNSS+INS RECEIVER DELIVERS 3D POSITION, VELOCITY AND ATTITUDE



### SPAN: WORLD LEADING GNSS+INS TECHNOLOGY

Synchronous Position, Attitude and Navigation (SPAN) technology brings together two different, but complementary technologies: Global Navigation Satellite System (GNSS) positioning and inertial navigation. The absolute accuracy of GNSS positioning and the stability of Inertial Measurement Unit (IMU) gyro and accelerometer measurements are tightly coupled to provide an exceptional 3D navigation solution that is stable and continuously available, even through periods when satellite signals are blocked.

### SPAN-CPT OVERVIEW

SPAN-CPT is a compact, single enclosure GNSS+INS receiver, powered by NovAtel's world class OEM6® technology. Capable of delivering up to centimetre level accuracy, customers can choose from a variety of positioning modes to ensure they have the optimal level of accuracy for their application. Available modes include SBAS, PPP and RTK.

The IMU components within the SPAN-CPT enclosure are comprised of Fiber Optic Gyros (FOG) and Micro Electromechanical System (MEMS) accelerometers, maximizing price/performance value. FOGs offer exceptionally long life and stable performance compared with other similar gyro technologies.

### SPAN-CPT ADVANTAGES

The tight coupling of the GNSS and IMU measurements delivers the most satellite observations and the most accurate, continuous solution possible. Further, SPAN-CPT is comprised entirely of commercial components, which means cross-border difficulties involved with traditional GNSS+INS systems are greatly minimized.

### IMPROVE SPAN-CPT ACCURACY

Take advantage of our Advance® RTK as well as support for satellite based augmentation systems such as SBAS to improve real-time performance and accuracy. For more demanding applications Inertial Explorer® post processing software from our Waypoint® Products Group can be used to post-process SPAN data and offers the highest level of accuracy.

### BENEFITS

- + Continuous, stable positioning
- + Easy to integrate into space constrained applications
- + Minimizes import/export issues
- + Withstands harsh environments
- + Innovative OEM6 technology

### FEATURES

- + Fiber optic gyros and MEMS accelerometers
- + SBAS, NovAtel CORRECT™ PPP and RTK support
- + 100 Hz raw data and solution
- + Wheel sensor input for ground applications
- + Optional dual antenna

If you require more information about our SPAN products, visit [www.novatel.com/span](http://www.novatel.com/span)

# SPAN-CPT™

## SPAN SYSTEM PERFORMANCE<sup>1</sup>

### Horizontal Position Accuracy (RMS)

Single point L1/L2	1.2 m
SBAS <sup>2</sup>	0.6 m
DGPS	0.4 m
NovAtel CORRECT™	
» PACE™	0.15 m
» TerraStar™	0.1 m
» RT-2®	1 cm + 1 ppm

### Data Rate

GPS measurement	20 Hz
GPS position	20 Hz
IMU measurement	100 Hz
INS solution	Up to 100 Hz

**Time accuracy<sup>3</sup>** 20 ns RMS

**Max Velocity<sup>4</sup>** 515 m/s

## IMU PERFORMANCE

Gyro technology	FOG
Gyro output range	±375°/s
Gyro bias	20°/hr
Gyro bias stability	±1°/hr
Gyro scale factor	1500 ppm
Angular random walk	0.0667°/√hr (max)
Accelerometer range	±10 g
Accelerometer bias	50 mg
Accelerometer bias stability	±0.75 mg
Accelerometer scale factor	4000 ppm

## PHYSICAL AND ELECTRICAL

### Dimensions

152 x 168 x 89 mm

**Weight** 2.28 kg

### Power

Power consumption 16 W Max

Input voltage +9 to +18 VDC

### Antenna Port Power Output

Output voltage +5 VDC

Maximum current 100 mA

### Connectors

Power and I/O	MIL-DTL-38999 Series 3
Antenna Input	TNC Female

## COMMUNICATION PORTS

RS-232 UART COM	2
USB Device	1
CAN	1
Event Input Trigger	1
Configurable PPS	1

## ENVIRONMENTAL

### Temperature

Operating -40°C to +65°C

Storage -50°C to +80°C

**Humidity** 95% non-condensing

### Waterproof

MIL-STD-810F, 506.4, Procedure I

## INCLUDED ACCESSORIES

- Combined I/O and power cable

## OPTIONAL ACCESSORIES

- GPS-700 series antennas (dual-frequency required)
- ANT series antennas (dual-frequency required)
- RF cables—5, 10 and 30 m lengths
- Inertial Explorer post-processing software

### Optional Dual Antenna<sup>5</sup>

Baseline	Accuracy
0.5 m	0.4°
1.0 m	0.2°
2.0 m	0.1°

For the most recent details of this product:  
[www.novatel.com/products/span-gnss-inertial-systems/span-combined-systems/span-cpt/](http://www.novatel.com/products/span-gnss-inertial-systems/span-combined-systems/span-cpt/)

## novatel.com

sales@novatel.com

1-800-NOVATEL (U.S. and Canada) or 403-295-4900

China  
0086-21-54452990-8011

Europe 44-1993-848-736

SE Asia and Australia  
61-400-883-601

**Version 7** Specifications subject to change without notice.

©2014 NovAtel Inc. All rights reserved.

NovAtel, Inertial Explorer, AdVance, Waypoint, SPAN and OEM6 are registered trademarks of NovAtel Inc.

SPAN-CPT, NovAtel CORRECT and PACE are trademarks of NovAtel Inc.

D12768 February 2014

Printed in Canada.



Statements related to the export of products are based solely on NovAtel's experience in Canada, are not binding in any way and exportability may be different with respect to the export regulations in effect in another country. The responsibility for re-export of product from a Customer's facility is solely the responsibility of the Customer.

## PERFORMANCE DURING GNSS OUTAGES<sup>1</sup>

Outage Duration	Positioning Mode	POSITION ACCURACY (M) RMS		VELOCITY ACCURACY (M/S) RMS		ATTITUDE ACCURACY (DEGREES) RMS		
		Horizontal	Vertical	Horizontal	Vertical	Roll	Pitch	Heading
0 s	RTK <sup>6</sup>	0.02	0.03	0.015	0.010	0.020	0.020	0.060
	SP	1.00	0.60	0.020	0.010	0.020	0.020	0.060
	PP <sup>7</sup>	0.01	0.02	0.020	0.010	0.015	0.015	0.030
10 s	RTK <sup>6</sup>	0.26	0.16	0.045	0.024	0.030	0.030	0.080
	SP	1.21	0.73	0.050	0.024	0.030	0.030	0.080
	PP <sup>7</sup>	0.02	0.02	0.020	0.020	0.015	0.015	0.030
60 s	RTK <sup>6</sup>	6.09	2.05	0.255	0.080	0.045	0.045	0.101
	SP	7.04	2.62	0.260	0.080	0.045	0.045	0.101
	PP <sup>7</sup>	0.23	0.07	0.030	0.020	0.016	0.016	0.032

1. Typical values. Performance specifications subject to GPS system characteristics, US DOD operational degradation, ionospheric and tropospheric conditions, satellite geometry, baseline length, multipath effects and the presence of intentional or unintentional interference.

2. GPS only.

3. Time accuracy does not include biases due to RF or antenna delay.

4. Export licensing restricts operation to a maximum of 515 metres/second.

5. Dual antenna requires a second NovAtel receiver to be paired with the SPAN-CPT.

6. 1 ppm should be added to all values to account for additional error due to baseline length.

7. Post-processing accuracy using Inertial Explorer processing software.

