



L1/L2 GPS+GLONASS Receiver and Antenna Ideal for Harsh Environments

Benefits

Scalable dual-constellation, dual-frequency performance

Smooth, consistent positions for pass-to-pass accuracy

Rugged design for on-machine applications

Features

GPS and GLONASS satellite capability

GL1DE® and AdVance® RTK positioning

Robust power handling for 12 V to 24 V vehicle power

Integrated GNSS Design

NovAtel's ergonomically designed SMART-MR10 provides an integrated L1/L2 GPS+GLONASS receiver and antenna in a single compact enclosure. Designed to meet or exceed stringent MIL-STD-810G specifications, the SMART-MR10's rugged metal housing ensures high performance even in the most challenging work environments.

Precision Performance

The SMART-MR10 features 14 channels for each of L1 and L2 GPS and 12 channels for each of L1 and L2 GLONASS code and phase tracking. An additional two channels are dedicated for Satellite-Based Augmentation System (SBAS: WAAS, EGNOS and MSAS) signals as well as one channel for L-band.

Multiple Interfaces Deliver Maximum Flexibility

Three NMEA 0183 compatible RS-232 serial ports, one NMEA2000 compatible CAN port and built-in Bluetooth ensure the SMART-MR10 delivers maximum flexibility. An Emulated Radar ground speed output, a one pulse per second output (1 PPS) and an event mark input are also provided. Three daylight readable status LEDs simplify in-field diagnoses.

Smooth, Pass-to-Pass Accuracy with GL1DE Technology

NovAtel's exclusive GL1DE technology is integrated into every SMART-MR10 antenna. GL1DE uses the very accurate carrier phase calculations to provide ultra smooth positions and excellent pass-to-pass accuracy for agricultural applications. GL1DE functions autonomously and with most available corrections services. It will also bridge through short periods of poor satellite availability. GL1DE's steady, smooth output is especially well suited for manual guidance and autosteer installations.

If you require more information about SMART, visit novatel.com/products/gnss-receivers/smart-antennas



novatel.com

sales@novatel.com

1-800-NOVATEL (U.S. and Canada)
or 403-295-4900

China 0086-21-54452990-8011

Europe 44-1993-848-736

SE Asia and Australia 61-400-833-601

Performance

Channel Configuration

14 GPS L1, 14 GPS L2
 12 GLONASS L1, 12 GLONASS L2 (optional)
 2 SBAS¹
 1 L-band

Horizontal Position Accuracy (RMS)²

Autonomous (L1)	1.5 m
Autonomous (L1/L2)	1.2 m
SBAS	0.6 m
CDGPS	0.6 m
DGPS	0.4 m
OmniSTAR	
VBS	0.6m
XP	0.15m
HP	0.1m
RT-20 ^{®3} (optional)	0.2 m
RT-2 ^{™3} (optional)	1 cm+1ppm

Measurement Precision

	GPS	GLONASS
L1 C/A Code	4 cm	15 cm
L1 Carrier Phase	0.5 mm	1.5 mm
L2 P(Y) Code	8 cm	8 cm
L2 Carrier Phase	1.0 mm	1.5 mm

Maximum Data Rate

Measurements 1Hz, 5Hz, 10Hz, 20Hz⁴
 Position 1Hz, 5Hz, 10Hz, 20Hz⁴

Time to First Fix

Cold Start⁵ 65 s
 Hot Start⁶ 35 s

Signal Reacquisition

L1 0.5 s (typical)
 L2 1.0 s (typical)

Time Accuracy⁷ 20 ns RMS

Velocity Accuracy⁸ 0.03 m/s RMS

Physical and Electrical

Dimensions 233 mm x 232 mm
 x 89 mm height

Weight 1.9 kg

Power
 Input Voltage +9 to +36 VDC
 Power Consumption 3.7 W (typical)

Connector
 23-pin Tyco Ampseal

Mounting
 1/4 NC and M6 mounting holes

Communication Ports

3 RS-232 serial ports
 (1 port configurable to RS-422)
 1 CAN Bus NMEA 2000⁹
 1 Bluetooth
 Emulated Radar
 1 PPS
 Event mark input

Environmental

Temperature
 Operating -40°C to +70°C
 Storage -55°C to +90°C

Humidity 95% non-condensing

Vibration
 Random MIL-STD-202G
 Sinusoidal ASAE EP455

Shock MIL-STD-810G, 516.6

Immersion MIL-STD-810G, 512.5

Blowing Rain MIL-STD-810G, 506.5

Water Jets IEC 60529 IPX6

Object Ingress and Immersion

IEC 60529 IP67
 Aggravated Cycle MIL-STD-810G, 507.5

Compliance

Emissions FCC, CE, Industry Canada, BT SIG
 Immunity CE

Vehicular Standards

ISO 7637: Compliance ensures product's ability to operate through vehicular electrical system surges (including inductive load switching transients, crank cycle and load dump)

ISO 15003: Compliance ensures product's ability to withstand vehicular electrical system abnormal conditions (short circuits to battery or ground, overvoltage reverse polarity and abnormal power voltage)

Optional Accessories

- Mounting plate
- Quick release kit
- Interface cables



Version 2 - Specifications subject to change without notice.

©2011 NovAtel Inc. All rights reserved.

NovAtel, AdVance, GL1DE, and RT-20 are registered trademarks of NovAtel Inc. SMART-MR10 and RT-2 are trademarks of NovAtel Inc.

The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by NovAtel Inc. is under license. Other trademarks and trade names are those of their respective owners.

OmniSTAR is a registered trademark of OmniSTAR Inc.

Printed in Canada. D14061

SMART-MR10 April 2011

For the most recent details of this product:

novatel.com/assets/Documents/Papers/SMART-MR10.pdf

¹ Satellite Based Augmentation Systems (SBAS) include WAAS (North America), EGNOS (Europe) and MSAS (Japan).

² Typical values. Performance specifications subject to GPS system characteristics, US DOD operational degradation, ionospheric and tropospheric conditions, satellite geometry, baseline length, multipath effects and the presence of intentional or unintentional interference sources.

³ Expected accuracy after convergence. RT-20 and RT-2 are independent of GL1DE.

⁴ Contact NovAtel Inc. for 20Hz operation.

⁵ Typical value. No almanac or ephemerides and no approximate position or time.

⁶ Typical value. Almanac and recent ephemerides saved and approximate time entered.

⁷ Relative time accuracy does not include biases due to RF or antenna delay.

⁸ Export licensing restricts operation to a maximum velocity of 515 metres per second.

⁹ Fixed CAN messages in firmware.

