

GPS ANTI-JAM TECHNOLOGY (GAJT®) ANTENNA ELECTRONICS IN A CARD STACK BRACKET

EASY TO INTEGRATE

The GAJT-AE-R contains the GAJT-AE card stack (digital card and RF card) installed into a mounting bracket to simplify integration into a custom designed enclosure. The mounting bracket provides thermal dissipation for the GAJT-AE-R card stack which is then mounted to a thermally conductive surface in a user enclosure.

JAMMING AND INTERFERENCE ARE HERE TO STAY

Jamming and interference, whether intentional or unintentional, can seriously degrade GPS position, navigation and time availability—even to the point of total solution denial. Jammers create excessive noise, overpowering the low power GPS signals and saturating the electronics in a GPS receiver front end. Methods are needed to suppress this interference so your GPS receiver continues to operate.

WHO IS IT FOR?

GAJT-AE-R is designed for size and weight constrained applications such as small airborne and ground unmanned platforms, where it is preferable to mount the antenna electronics inside the vehicle. Users can select from a variety of 4-element CRPA antenna arrays.

LEADING EDGE TECHNOLOGY

Interference mitigation is achieved by applying proprietary digital null forming algorithms to the signals, creating dynamic nulls to give protection against narrowband and broadband interference sources. The unit comprises Radio Frequency (RF) front ends and null forming electronics. DC power is supplied via a dedicated LEMO® connector. Integration to your GPS receiver is seamless. Any 4-element CRPA can be used. We recommend antennas from Antcom Inc., either from their standard range or designed for custom form-factors.

HOW IT WORKS

GAJT mitigates interference by creating nulls in the antenna gain pattern in the direction of jammers, providing significant anti-jam protection even in dynamic multi-jammer scenarios. The output of the GAJT-AE-R is a standard Radio Frequency (RF) feed, suitable for input to legacy GPS receivers.

BUILT FOR THE FUTURE

The wide bandwidth ensures future compatibility with M-Code GPS.

BENEFITS

- + Low cost anti-jam protection for small platforms
- + Easy to integrate
- + Anti-jam protection in dynamic multi-jammer scenarios
- + Compatible with legacy GPS receivers
- + Works with most 4-element antenna arrays (supplied separately)

FEATURES

- + Affordable protection for GPS position, velocity and time
- + Up to 40 dB of additional anti-jamming protection
- + Simultaneous L1 and L2
- + Adaptive digital nulling
- + Built in test and jamming status included in RS-232 output

For more information about GAJT, visit www.novatel.com/GAJT or email GAJT@novatel.com

GAJT-AE-R™



PERFORMANCE

GNSS (GPS) Signals

Center frequency	
L1	1575.42 MHz
L2	1227.6 MHz

INTERFERENCE REJECTION

Simultaneous L1 and L2

Typical wideband suppression	40 dB
Number of simultaneous nulling directions	3

ANTENNA ARRAY OPTIONS

L1 and L2

- » 4 element Antcom 3.5 inch
- » 4 element Antcom 4.25 inch
- » 4 element Antcom 5 inch

RF PORTS

RF inputs	4 x 50 ohm SMA
RF outputs	1 x 50 ohm SMA

POWER & COMMUNICATION PORTS

Power	Molex x1
Data	Molex x1

PHYSICAL AND ELECTRICAL

Power

Power consumption	15 W
Input voltage	+10 to +28 VDC

Dimensions 150 x 120 x 35 mm

Weight 585 g

ENVIRONMENTAL

MIL-STD-810G

Temperature

Operating	-40°C to +71°C
Storage	-55°C to +85°C

Humidity 95% non-condensing

Vibration MIL-STD-202G
ASAE EP455

Shock MIL-STD-810G(CH1), 516.7

TIMING

Fixed timing delay

CRPA ANTENNA

LNA Gain 26 dB to 30 dB

ACCESSORIES

- Optional power and data cable

EXPORT APPROVALS

Canadian Controlled Goods

OTHER GAJTS

GAJT-710ML



- Single enclosure system for land and fixed applications
- 7-element antenna array
- Easy to integrate, ideal for retrofitting

GAJT-710MS



- Single enclosure system for warships and other marine vessels
- 7-element antenna array
- Easy to integrate, ideal for retrofitting

4-ELEMENT ANTENNA ARRAY

A 4-element antenna array allows gain pattern shapes to be changed in response to interference. Provides 3 independent nulls.

For more information about GAJT, visit www.novatel.com/GAJT or email GAJT@novatel.com

novatel.com

sales@novatel.com

1-800-NOVATEL (U.S. and Canada)
or 403-295-4900

Europe 44-1993-848-736

SE Asia and Australia 61-400-883-601

Version 0B

Specifications subject to change without notice.

©2018 NovAtel Inc. All rights reserved.

NovAtel and GAJT are registered trademarks of NovAtel Inc.

D24166 June 2018

Printed in Canada.

